

WEED USA, LLC

WEED 125-EX / 125-TOUR (X-ONE25, 3/4Weed) STRINGING INSTRUCTIONS

RECOMMENDED STRING TYPES :

In this model, almost any string will propel the ball well. However, a few stringing set-ups ARE KNOWN TO FEEL, SOUND AND PLAY SUPERBLY. They are:

1. 17 ga. **GAMMA TNT2 PRO PLUS** at any tension! Recommended especially for players who hit the ball flat, it is perfect for those who prefer a livelier response and more power. (16 ga. **GAMMA 2** is very similar - just not quite as crisp of a feel as the Pro, yet its slightly thicker gauge is more durable). Also quite good are: **WEED Black Synthetic Gut 16, 17** (45' sets), Gamma TNT2 16, 17, 18 or Ruff 16 (for Spin) **Gut Lovers: try Wilson NXT or Gamma Professional.**
2. For "Hard Hitters" who need maximum stringbed stiffness and/or stringbreakers needing greater durability, we recommend **FORTEN THIN BLEND (18 ga. Kevlar for the Mains paired with Sweet 17 synthetic crosses)**. Other similar kevlar products will work too, but beware: many of the pre-packaged sets may not be long enough (we stock the Thin Blend in reels and will be happy to cut "WEED length sets" of 25' kevlar and 20' SG). (*Suggested Tension Range for Kevlar Mains or Luxillion Big Banger / Polyester Strings: 60-65 lbs., max = 70 lbs.*).
3. For sore elbow, arm or shoulder relief: **Gamma TNT Rx 16 or 17** (if installed using our LP stringing method it will be even more beneficial - see description below).

TENSION : **MAXIMUM STRING TENSION IS 75 LBS. (KEVLAR /Polyester MAX = 70 LBS!)**
IT IS IMPORTANT (and required for warranty) TO STRING THE CROSSES AT 5 LBS. LESS THAN THE MAINS.

When selecting a tension - fit the tension to what players are used to - they can't change their habits!

If they have been playing a small racquet at higher tensions: give them higher tensions in the WEED and consider a stiffer string.

If they're used to lower tensions in a larger frame, 45-60 lbs. in the WEED X-ONE25 series models will probably fit them.

*******"SLACKING OFF" tensions progressively by 5, 10 and 15 lbs. on the outside 3 mains and top & bottom 3 crosses are MANUFACTURER'S REQUIREMENT FOR FRAME WARRANTY.** This also provides an even broader sweetspot, more power on balls hit next to the frame, and eases initial shock on the arm. (The top 3 X's would slack by 15, then 10, and then 5 lbs. off the base racquet tension, and the bottom 3 X's would slack by 5, then 10, and then 15 lbs.).

Note: WEED highly recommends their special L.P. ("Live Periphery") Stringing process for these models (description below). (*Instructions available*)

Conventional stringing procedures are outlined on the reverse side of this sheet.

L.P. instructions (and assistance via the 800#) are available upon request.

L.P. Stringing creates nearly frame to frame Power Zone. It features a more lively periphery (area out near the frame), for greater depth on off-center hits (and less shock to the arm on such hits!), which converts into much steadier, controlled play. [This progressive tension pattern also incorporates a second, much stretchier string (Durbin CDT) in the last 2 mains and crosses, to help increase the power in that area. The Durbin string is available through WEED].

**IT IS IMPORTANT (and required for the warranty) TO
STRING THE CROSSES AT 5 LBS. LESS THAN THE MAINS.**

LENGTH : Depends on the stretchiness of the string!

42 FEET *is enough in most cases*

ONE SET (40 FT.) OF GAMMA PRO OR GAMMA 2 will string the whole racquet at 65 lbs. or higher (usually).

FOR 1 PIECE stringing use: 11 1/4 ft. for the **SHORT SIDE OF MAINS**
(add 3 to 4 inches if under 60 lbs.)

FOR 2 PIECE stringing: **MAINS = 22 1/2 to 24 ft.**

IF KEVLAR: 24 FT.

CROSSES = 18 ft.

PATTERN : 18 MAINS X 20 CROSSES

MAINS START AT THE THROAT.

**MAINS SKIP HOLE NUMBERS 8 AND 10 AT TIP & THROAT AND
NUMBER 11 THROAT. TIE OFF SHORT SIDE OF MAINS IN 4 H OR 7 H.**

**WHEN YOU GET TO THE 3RD TO THE LAST MAIN (from the outside, on both sides),
DROP THE TENSION BY 5 LBS. DROP THE TENSION BY ANOTHER 5 LBS.
(total of 10 lbs. off the base tension) IN THE 2ND TO LAST MAIN AND 5 MORE LBS.
(total of 15) IN THE LAST (outside) MAIN.
(ie. if stringing the racquet at 60 lbs., the last 3 mains would be at 55, 50 and 45 lbs.)
(WARRANTY IS NOT VALID UNLESS the string tension is slacked.**

TOP CROSS THROUGH HOLE NUMBER 8 TIP.

CROSSES SKIP HOLE NUMBER 9 AT THE TIP & THROAT.

SHARED HOLES = NUMBER 11 TIP AND NUMBER 12 THROAT.

BOTTOM CROSS THROUGH 8 THROAT. TIE OFF IN NUMBER 6 THROAT.

*******"SLACKING OFF" tensions progressively by 5, 10 and 15 lbs. on the outside 3 mains
and top & bottom 3 crosses are MANUFACTURER'S REQUIREMENT FOR FRAME WARRANTY.
This also provides an even broader sweetspot, more power on balls hit next to the frame,
and eases initial shock on the arm. (The top 3 X's would slack by 15, then 10, and then 5
lbs. off the base racquet tension, and the bottom 3 X's would slack by 5, then 10, and then
15 lbs.).**

WEED USA, LLC

**5780 Harrow Glen Ct. Galena, Ohio 43021 (740) 548-3881
1-800-WEED-RKT web: www.weedusa.com**